

# **GEAR RACK ADJUSTMENT WHEEL FOR CIRCULAR KNITTING MACHINES**

## **FIELD OF THE INVENTION**

The present invention relates to a gear rack adjustment  
5 wheel for circular knitting machines to adjust an adjustable  
sliding block to a correct position for a smooth and precise  
knitting operation.

## **BACKGROUND OF THE INVENTION**

Referring to FIG.1, a conventional cam fine-tuning  
10 apparatus includes a straddle dock 11, a sliding block 12  
coupled on the straddle dock 11 that has a plurality of cams 16  
fastened thereon, a fine-tuning assembly 13 located on the  
straddle dock 11 that has a screw thread, a retaining member  
14 located respectively on an upper edge and a lower edge of  
15 the straddle dock 11, and a spring 15 located between the  
retaining member 14 at the lower edge of the straddle dock 11  
and the sliding block 12.

The fine-tuning assembly 13 has a first sloped surface 131  
extending into a trough 121 of the sliding block 12 to be in  
20 contact with a second sloped surface 1211 formed on the  
trough 121. When the fine-tuning assembly 13 is turned, it is  
moved outwards from the straddle dock 11 along the screw  
thread. The fine-tuning assembly 13 presses the sliding block  
12, with the first sloped surface 131 ramming the second  
25 sloped surface 1211 so that the sliding block 12 is pushed

downwards along the first sliding surface 131. By contrast, when the fine-tuning assembly 13 is turned in the reverse direction, it is moved into the straddle dock 11 along the screw thread, and the spring 15 located between the retaining member 14 at the lower edge of the straddle dock 11 and the sliding block 12 will push the sliding block 12 upwards along the first sloped surface 131.

The spring 15, located between the retaining member 14 at the lower edge of the straddle dock 11 and the sliding block 12 is in a compressed state. After repeated use elastic fatigue or fatigue failure occurs, i.e. the elasticity weakens or disappears altogether. As a result, the sliding block 12 cannot return to its original position. Therefore, the circular knitting machine cannot operate properly and fails to knit correctly. Moreover, the service life of the spring 15 is limited and often requires replacement. Repairing a knitting machine is both costly and time consuming. Replacing parts not only increases overheads, while the machine is out of commission throughput is decreased.

## 20 **SUMMARY OF THE INVENTION**

Therefore the present invention aims at providing an improved fine-tuning mechanism that can precisely adjust the sliding block to the correct position, thus enabling the circular knitting machine to achieve a smooth and precise knitting operation.

The primary object of the invention is to solve the aforesaid disadvantages. The invention includes an adjustable sliding block which has a gear rack and an adjustment wheel containing a screw thread. The screw thread couples to the gear rack so that the adjustable sliding block can slide along the track of the adjustment wheel. Thereby the sliding block can be adjusted to the correct position to achieve a smooth and precise knitting operation.

The gear rack adjustment wheel according to the invention includes a holding deck located on a circular knitting machine, an adjustable sliding block slides along the bottom of the holding deck which has a gear rack formed on a lateral side, a sliding trough in the holding deck to communicate with the adjustable sliding block, an aperture formed on one side of the holding deck, and an adjustment mechanism which includes an adjustment wheel and an anchor pin for the adjustment wheel. The adjustment wheel is housed in the sliding trough which communicates with the adjustable sliding block so that the adjustment wheel can be in contact with the adjustable sliding block and adjust the adjustable sliding block. The adjustment wheel has a screw thread which may be coupled with the gear rack of the adjustable sliding block, a nut which has a scale to indicate the adjustment degree, and an annular ring spaced from the nut to form a gap to be wedged by the anchor pin to anchor the adjustment wheel at a desired

position. The anchor pin is housed in the aperture in the holding deck.

Through the movement of the adjustment wheel, the relative position of the gear rack of the adjustable sliding block and screw track of the adjustment wheel may be altered,  
5 and the position of the adjustable sliding block may be adjusted.

The foregoing, as well as additional objects, features and advantages of the invention will be more readily apparent  
10 from the following detailed description, which proceeds with reference to the accompanying drawings.

### **BRIEF DESCRIPTION OF THE DRAWINGS**

FIG. 1 is a schematic view of a conventional cam fine-tuning mechanism. .

15 FIG. 2 is an exploded view of the present invention.

FIG. 3 is a perspective view of the present invention.

FIGS. 4A and 4B are cross sections taken on line 4A-4A in FIG. 3 showing operating condition.

### **DETAILED DESCRIPTION OF THE PREFERRED**

#### **EMBODIMENT**

Please refer to FIG. 2, the gear rack adjustment wheel for circular knitting machines according to the invention includes a holding deck 1, an adjustable sliding block 2, slides in a sliding track 52 formed at the bottom of the holding deck 1  
25 that has a gear rack 6 formed on a lateral side thereof, and an

adjustment mechanism which includes an adjustment wheel 3 with a screw thread 7 formed thereon and an anchor pin 4 for the adjustment wheel. The holding deck 1 has a sliding trough 5 which reaches the adjustable sliding block 2 so that the  
5 adjustment wheel 3 can be in contact with the adjustable sliding block 2. The holding deck 1 further has an aperture 51 to receive an anchor pin 4 to anchor the adjustment wheel 3. The adjustment wheel 3 includes a screw thread 7 to couple with the gear rack 6, an annular ring 10 located on an  
10 extension of the screw thread 7, a nut 8 with a scale formed thereon, and a gap 9 formed between the nut 8 and the annular ring 10 to receive the anchor pin 4 which has one end exposed through the aperture 51 of the holding deck 1.

Refer to FIG. 3 for the invention mounting on a circular  
15 knitting machine. The track of the screw thread 7 corresponds to the gear rack 6. Turning the adjustment wheel 3, allows the adjustable sliding block 2 to move on the sliding track 52. The scale on the adjustment wheel 3 and the other adjustment wheels 3 allows the other adjustable sliding blocks 2 to be  
20 moved to the same position. Therefore the operation of the circular knitting machine is more smooth and precise.

Referring to FIGS. 4A and 4B, the adjustment wheel 3 is housed in the sliding trough 5 of the holding deck 1 to couple with the gear rack 6 of the adjustable sliding block 2. The  
25 anchor pin 4 runs through the aperture 51 of the holding deck

1 to wedge in the gap 9 between the nut 8 and the annular ring  
10 to anchor the adjustment wheel 3 to a selected location in  
the holding deck 1. When the adjustment wheel 3 is turned,  
the screw thread 7 also turns to drive the corresponding gear  
5 rack 6 so that the entire adjustable sliding block 2 can slide  
along the sliding track 52.

While the preferred embodiment of the invention has been  
set forth for the purpose of disclosure, modifications of the  
disclosed embodiment of the invention as well as other  
10 embodiments thereof may occur to those skilled in the art.  
Accordingly, the appended claims are intended to cover all  
embodiments which do not depart from the spirit and scope of  
the invention.